

# GB113 SWFR Bolt





#### Reflective

De-lustered fibers and lightning bolt shaped angles dull and refract light for low-luster appearance



## **Durable**

2x wear resistance over industry standard yarn



### **Bolt Fiber**

Enhanced resistance to matting, perfect for high-traffic areas



# **UV-Resistant**

Protects against harmful UV rays and extends the life of the turf

Designed as a multi-purpose turf for fringes, poolsides and paver strips, the SWFR continues to be a standout style across the globe. Bolt Turf Blade

Turf Thatch

Fines / 98% compaction

Crusher Run / 95% compaction

Geotextile (optional)

Sub-Base





	PROPERTY	IMPERIAL	METRIC	DESCRIPTION
PRODUCT	Fiber Type	100% Polyethylene		
PROPERTIES	Total Fiber Mass	10,800 denier 4,500 denier	12,000 dtex 5,000 dtex	6 Ply PE Mono 8 Ply TXT PE
	Finished Pile Height	1.5 in.	38.1 mm.	
	Colors	(301) Spring Green - Green Thatch (302) Olive Blend - Green Thatch (303) Field Green/Lime - Jute/Green Thatch (304) Field Green/Olive - Jute/Green Thatch		
	Tufting Gauge	1/4 in.	6.35 mm.	
	Primary Backing	7 oz/yd²	237.34 g/m²	Stabilized Dual Layered Woven Polypropylene
	Secondary Backing	20 oz/yd²	678.12 g/m²	Urethane
PERFORMANCE PROPERTIES	Tufted Face Weight	58 oz/yd²	1,966.53 g/m²	ATSM D418
	Total Weight	85 oz/yd²	2,881.99 g/m²	ATSM D418
PACKAGING	Item Number			GB113
	Tufted Roll Width	15 ft.	4.57 m.	





Southwest Greens International warrants to the original purchaser of the turf that for fifteen (15) years from the date of synthetic turf installation, the turf, when installed and maintained as recommended by the yarn and turf manufacturer, will retain at least 50% of its pile fiber. If any area or portion of the turf substantially changes, as distinguished from a change in texture, or if pile heights decrease 50% or more within fifteen years after its initial installation, Southwest Greens International will have all such areas or portions replaced with new turf of equivalent quality, excluding installation costs. Southwest Greens International also warrants that at the time of the initial turf installation, the synthetic turf will be free of manufacturing defects. Slight color changes will occur over the lifetime of this turf/carpet and is not considered an issue or basis for claim. All labor cost involved with the removal of the affected turf/carpet and reinstallation of the replacement will be the responsibility of the purchaser.

\*For full terms, please see the 15 year warranty agreement.

<sup>\*</sup> Tufted pile height as standard. Pile height will draw down slightly during secondary backing process.

<sup>\*\*</sup> Tufting gauge and stitch rate as manufactured standard. Values will change slightly during secondary backing process.

<sup>\*\*\*</sup> Standard roll lengths. Roll lengths may vary. Custom roll lengths and cuts are available upon request.

<sup>\*\*\*\*</sup> All specifications subject to manufacturing tolerances of  $\pm$ /-5%.